

FEATURES

- 100% ED
- IP65
- Tapped hole for mounting
- Zinc plated

- Other voltages including AC available
- Metal armatures available
- Optional connectors
- Assumed operating temperature 20°C



Model Number	Holding Force	Power Consumption		Weight	Dimensions			
		12vdc	24vdc		А	В	С	D
GM3522	150N	3.8W	4.4W	160g	Ø35mm	22mm	M6	10mm
GM4530	290N	5.2W	4.1W	290g	Ø45mm	30mm	M8	15mm
GM5530	660N	4.2W	3.6W	440g	Ø55mm	30mm	M8	15mm
GM6533	800N	4.3W	4.4W	670g	Ø65mm	33mm	M10	15mm
GM9535	1200N	7.6W	7.3W	1600g	Ø95mm	35mm	M12	20mm



www.pennyandgiles.com

Penny+Giles

Solenoids, joysticks and position sensors for commercial and industrial applications.

Unit 50, Innovation House South Church Enterprise Park Bishop Auckland County Durham DL14 6XB United Kingdom +44 (0) 1388 771200 +44 (0) 1388 772490 Fax solenoids@pennyandgiles.com

665 North Baldwin Park Boulevard City of Industry, CA 91746 USA +1 626 480 2150 +1 626 369 6318 Fax us.sales@pennyandgiles.com

Straussenlettenstr. 7b 85053 Ingolstadt Germany +49 (0) 841 885567-0 +49 (0) 841 885567-67 Fax info@penny-giles.de

3-1-A, Xiandai Square, No 333 Xingpu Rd, Suzhou Industrial Park, 215126 China +86 512 6287 3380 +86 512 6287 3390 Fax sales@pennyandgiles.com.cn

The information contained in this brochure on product applications should be used by customers for guidance only. Penny+Giles Controls Ltd makes no warranty or representation in respect of product fitness or suitability for any particular design application, environment, or otherwise, except as may subsequently be agreed in a contract for the sale and purchase of products. Customers should therefore satisfy themselves of the actual performance requirements and subsequently the product's suitability for any particular design application and the environment in which the product is to be used.

Continual research and development may require change to products and specifications without prior notification.

All trademarks acknowledged.

© Penny+Giles Controls Ltd 2011

Innovation In Motion

