

Penny & Giles Hall-Effect Paddle Joystick JC1210

- Robust design for arduous applications
- Options for Overpress and Latch at ends of travel
- Soft Touch sections of the 'Tab'
- Under-panel depth minimized to 9 mm – Molex connector
- Three electrical termination options
- Rated for 5 million cycles up to start of overpress
- Hall-effect sensor technology
- Dual outputs with sense and voltage span options
- IP67 sealing above panel
- Two mounting panel fixing options in the one body design
- Color-coded 'Tab' options



The JC1210 builds on the success of the JC1200 and incorporates the same robust design with exceptional life and now offers the option of overpress and latch features at the ends of travel. This new joystick utilizes non-contacting, Hall-effect sensing technology for long-life integrity of the output signal. Operating feel has been an important part of this new development to make this unit as smooth and easy to operate as possible throughout a 5 million cycle-life to the start of overpress.

Hall-effect sensing eliminates contact wear and provides safety functionality via dual outputs, which can be set to positive or negative ramps, or a combination of both. Electronic robustness is assured with sealing of the internal PCB to a rating of IP67, while a joystick to panel rating of IP67 can be achieved.

The joystick is available with Overpress and Latch options at the ends of travel, which can be combined to meet your system needs to hold functions at full speed/float.

There are three options for electrical termination – integrated Molex connector, flying lead with Molex connector or header pins.

A soft-touch colored insert area of the paddle – which has a choice of nine colors – increases operator comfort and decreases the likelihood of finger-slip during operation.

SPECIFICATIONS

ELECTRICAL

| | |
|------------------------------|---|
| SUPPLY VOLTAGE | 5Vdc \pm 0.5Vdc |
| OUTPUT VOLTAGE (FACTORY SET) | 10% to 90% or 20% to 80% of the Supply Voltage |
| CENTER REFERENCE | 48.0% to 52.0% of supply voltage |
| OUTPUT SENSE | The dual outputs can be configured to have positive ramps, negative ramps or a combination of both. |
| CURRENT CONSUMPTION | < 25mA |
| CONNECTION | Integrated 7-way Molex or flying lead with 4-way Molex connector or 4-way header pins |


MECHANICAL

| | |
|--------------------------------------|--|
| BREAKOUT FORCE AT HANDLE TIP | 1.0N |
| OPERATING FORCE AT HANDLE TIP | 3.5N without overpress or latch at $\pm 30^\circ$ of full travel |
| OPERATING FORCE AT HANDLE TIP | 4.5N with overpress and/or latch at $\pm 40^\circ$ of full travel |
| OPERATING FORCE TO OPERATE OVERPRESS | 6 N |
| OPERATING FORCE TO ENGAGE LATCH | 8N |
| MECHANICAL ANGLE | $\pm 30^\circ$ without overpress/latch; $\pm 40^\circ$ with overpress/latch |
| MECHANICAL FEATURES | Overpress or Latch or Overpress and Latch at both ends of travel |
| GATE | Single axis |
| MECHANICAL LIFE | Linear section >5 million cycles Overpress >200,000 operations/overpress Latch >150,000 operations/latch |
| MTTFd | > 200 years |
| WEIGHT | Less than 40g |

ENVIRONMENTAL

| | | |
|--------------------------|------------------------------------|--|
| OPERATING TEMPERATURE | -40°C to 85°C | |
| STORAGE TEMPERATURE | -40°C to 85°C | |
| ENVIRONMENTAL PROTECTION | IEC 60529 | IP67 above panel, IP67 electronics and customer responsibility to seal the connector |
| EMC IMMUNITY LEVEL | ISO 11452-2 | 150V/m, 20MHz-1GHz |
| EMC EMISSIONS LEVEL | ISO 14982 or CISPR 25 ed.3 class 3 | 30MHz to 1GHz |
| ESD IMMUNITY LEVEL | ISO 10605 | ± 8 KV contact (including connector pins); ± 15 kV air discharge |
| VIBRATION - RANDOM | ISO 15003 | random, Level 1 in 3 axes |
| FREE FALL DROP | IEC 60068-2-31 | 1.0m on all edges and faces |
| SHOCK | EN 60068-2-27 | 40g, 6ms, Half Sine, 100 shocks in each of 3 directions |

COLOR TAB OPTIONS

| | | |
|--------|---|---------|
| BLACK |  | RAL9005 |
| GRAY |  | RAL7042 |
| WHITE |  | RAL9003 |
| YELLOW |  | RAL1023 |
| ORANGE |  | RAL2007 |
| RED |  | RAL3028 |
| PURPLE |  | RAL4006 |
| BLUE |  | RAL5010 |
| GREEN |  | RAL6038 |